



BOTTOM BAR LOCK		
TYPE	OPERATION	INTER LOCK
SLIDE BOLT	<input type="checkbox"/> INSIDE <input type="checkbox"/> OUTSIDE	<input type="checkbox"/>
CYLINDER	<input type="checkbox"/>	<input type="checkbox"/>
NO LOCKING	<input type="checkbox"/>	<input type="checkbox"/>

SLAT: #45  
 MAT'L: GALV. STEEL  
 FINISH: GREY PRIME  
 WINDLOCKS: NONE

BOTTOM BAR DETAIL  
 MAT'L: STEEL  
 FINISH: BRONZE PRIME

INSULATED SERVICE DOOR || BELT DRIVE MTR OPER || FACEMTD

- NOTES:
1. GENERAL SPECIFICATIONS SEE SHEET 1.
  2. APPROX. WT. OF DOOR IS \_\_\_\_\_ WT LBS.
  3. PROVIDE ADEQUATE CLEARANCE FOR WIRING MOTOR.
  4. ELECTRICAL INFORMATION:
    - VOLTAGE \_\_\_\_\_ PHASE \_\_\_\_\_
    - CONTROLLER NEMA 1
    - CONTROL STATION NEMA 1
    - PUSH BUTTON  SURFACE MTD
    - KEY STATION  FLUSH MTD
  5. DOOR DESIGNED FOR 25 CYCLES PER DAY.
  6. DOOR DESIGNED TO WITHSTAND 20 PSF WINDLOAD.
  7. THIS DRAWING COVERS GENERAL CONDITIONS, DIMS AND SPECIFICATIONS ONLY. DO NOT USE FOR INSTALLATION PURPOSES. INSTALLATION INSTRUCTIONS AND DIMENSIONS ARE INCLUDED WITH SHIPMENT.

DIMENSIONS AND CLEARANCES AS NOTED BY ASTERISK (\*) MUST BE FIELD CHECKED.

VERIFIED BY: \_\_\_\_\_ ON: \_\_\_\_\_

NO CANCELLATIONS OR RETURNS ON THIS ORDER:

Signature: \_\_\_\_\_

MAKE	HAND	ARCH. MARK	DOOR MARK
	AS SHOWN		
	OPPOSITE		

NO.	BY	DATE	REVISION
1			ORIGINAL DRAWING
2			
3			



JOB: \_\_\_\_\_

CONTRACTOR: \_\_\_\_\_

ARCHITECT: \_\_\_\_\_

DISTRIBUTOR: \_\_\_\_\_

DRAWING NO. \_\_\_\_\_ OF \_\_\_\_\_