

	Sectional Aluminum			Energy Efficient Polyurethane Insulated							Polystyrene Insulated			Ribbed Panel									
	MultiView	Full View		Super-Duty	Extra Heavy-Duty	Heavy-Duty		Heavy-Duty	Medium-Duty	Medium-Duty	Heavy-Duty	Medium-Duty	Medium-Duty	20-gauge	20-gauge	20-gauge	24-gauge	24-gauge	24-gauge	Nom. 24 ga	Nom. 24 ga	Nom. 24 ga	
	Heavy-Duty	Heavy-Duty	Medium-Duty			2742B	2742C																2747
<b>EXTERIOR PANEL DESIGN</b>																							
Flush					•							•											
Deep Ribbed													•	•	•	•	•	•	•	•	•	•	•
Pencil Groove				•		•	•		•	•	•	•											
Wide Groove																							
Stile and Rail	•	•	•																				
Aluminum Sections	•	•	•		•	•	•														•	•	•
<b>EXTERIOR PANEL TEXTURE</b>																							
Smooth	•	•	•																				
Stucco Embossment				•	•	•	•	•	•	•	•	•											
Woodgrain Embossment																							
<b>INTERIOR PANEL TEXTURE</b>																							
Smooth																							
Stucco Embossment				•	•	•	•	•	•	•	•	•											
<b>CONSTRUCTION LAYERS</b>																							
Steel + Insulation + Steel				•	•	•	•	•	•	•	•	•											
Steel + Insulation																							
Steel																							
Extruded Aluminum	•	•	•																				
<b>MINIMUM STANDARD WIDTH</b>	2' 0"	2' 0"	2' 0"	5' 0"	5' 0"	5' 0"	5' 0"	5' 0"	5' 0"	5' 0"	6' 0"	6' 0"	6' 0"	6' 0"	6' 0"	6' 0"	6' 0"	6' 0"	6' 0"	6' 0"	6' 0"	6' 0"	6' 0"
<b>MAXIMUM STANDARD WIDTH</b>	20' 2"	24' 2"	12' 2"	40' 2"	40' 2"	40' 2"	40' 2"	24' 2"	20' 2"	20' 2"	24' 2"	24' 2"	18' 2"	26' 2"	26' 2"	26' 2"	30' 2"	30' 2"	30' 2"	20' 2"	20' 2"	20' 2"	
<b>MAXIMUM STANDARD HEIGHT</b>	20' 1"	20' 1"	12' 1"	26' 1"	26' 1"	26' 1"	26' 1"	26' 1"	14' 1"	16' 1"	26' 1"	26' 1"	14' 1"	26' 1"	26' 1"	26' 1"	26' 1"	26' 1"	26' 1"	14' 1"	14' 1"	14' 1"	
<b>DOOR THICKNESS</b>	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	3" (7.6cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	1-5/8" (4.1cm)	1-3/8" (3.5cm)	1" (2.5cm)	2" (5.1cm)	2" (5.1cm)	1-3/8" (3.5cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	
<b>INSULATION<sup>1</sup></b>				Polyurethane	Polyurethane	Polyurethane	Polyurethane	Polyurethane	Polyurethane	Polyurethane	Polystyrene	Polystyrene	Polystyrene		Vinyl-Coated Polystyrene	Polystyrene		Vinyl-Coated Polystyrene	Polystyrene		Vinyl-Coated Polystyrene	Polystyrene	
<b>R-VALUE</b>				28.0 <sup>3</sup>	19.4 <sup>2</sup>	19.4 <sup>2</sup>	19.4 <sup>2</sup>	15.1 <sup>3</sup>	14.5 <sup>3</sup>	10.1 <sup>3</sup>	9.4 <sup>3</sup>	9.4 <sup>3</sup>	6.7 <sup>3</sup>		7.0 <sup>3</sup>	7.0 <sup>3</sup>		7.0 <sup>3</sup>	7.0 <sup>3</sup>		7.0 <sup>3</sup>	7.0 <sup>3</sup>	
<b>U-VALUE</b>				0.036	0.052	0.052	0.052	0.066	0.069	0.099	0.106	0.106	0.149		0.143	0.143		0.143	0.143		0.143	0.143	
<b>EXTERIOR STEEL THICKNESS</b>				27 ga	20 ga	27 ga	27 ga	27 ga	27 ga	.012"	24 ga	27 ga	27 ga	20 ga	20 ga	20 ga	24 ga	24 ga	24 ga	Nom. 24 ga	Nom. 24 ga	Nom. 24 ga	
<b>END STILE</b>				16 Ga	20 ga (16 ga optional)	20 ga (16 ga optional)	20 ga (16 ga optional)	16 Ga	20 ga	20 ga	20 ga	20 ga	20 ga	20 ga	19 ga (16 ga optional)	19 ga (16 ga optional)	19 ga (16 ga optional)	19 ga (16 ga optional)	19 ga (16 ga optional)	19 ga (16 ga optional)	19 ga (16 ga optional)	19 ga (16 ga optional)	
<b>CENTER STILE</b>														19 ga	19 ga	19 ga	19 ga	19 ga	19 ga	19 ga	19 ga	19 ga	
<b>HINGE REINFORCEMENT</b>				20 ga continous strip	20 ga continuous strip	20 ga backer plate	20 ga continous strip	20 ga continous strip	20 ga backer plate	20 ga backer plate	20 ga plate	20 ga plate	20 ga plate										
<b>BOTTOM WEATHER SEAL</b>																							
Aluminum Retainer	•	•	•								•		•	•	•	•	•	•	•	•	•	•	
Co-Extruded PVC				Triple Contact	Dual Contact	Dual Contact	Dual Contact	Triple Contact	Dual Contact	Dual Contact		Dual Contact											
<b>TOUNGE AND GROOVE JOINT</b>	•	•	•		•	•	•		•	•	•	•	•	•	•	•	•	•	•	•	•	•	
<b>WINDOW OPTIONS</b>																							
24" x 6"					•	•	•		•	•	•	•	•	•	•	•	•	•	•	•	•	•	
24" x 8"				•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
24" x 12"				•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
26" x 13"					•	•	•		•	•													
21" x 13"																							
41" x 13"																							
<b>PASS DOOR</b>					•	•	•																
<b>STEEL EXTERIOR COLORS</b>																							
True White (TW) / Commercial White (WH)				TW	TW	TW	TW	TW	TW	TW	TW	TW	TW	WH	WH	WH	WH	WH	WH	WH	WH	WH	WH
Almond (AL)													•										
Wicker Tan (WK)													•										
Sandtone (ST)				•		•	•	•	•	•	•	•	•										
Commercial Gray (CY)				•		•	•	•	•	•	•	•	•				•	•	•	•	•	•	•
Commercial Brown (CB)				•		•	•	•	•	•	•	•	•				•	•	•	•	•	•	•
Commercial Black (BG)*																	•	•	•	•	•	•	•
Amarr Color Zone*				•	•	•	•	•	•	•	•	•	•										
<b>HIGH CYCLE SPRINGS TO 100K</b>	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
<b>WIND LOAD<sup>4</sup> AVAILABLE</b>	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
<b>WARRANTY<sup>5</sup></b>																							
Paint Finish	5 Years <sup>6</sup>	5 Years <sup>6</sup>	5 Years <sup>6</sup>	10 Years	10 Years	10 Years	10 Years	10 Years	10 Years	10 Years	10 Years	10 Years	10 Years	10 Years	10 Years	10 Years	10 Years	10 Years	10 Years	10 Years	10 Years	10 Years	10 Years
Workmanship/Hardware	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year

<sup>1</sup> Insulation has passed self-ignition, flamespread and smoke developed index fire testing. <sup>2</sup> Amarr 2042 and 2742 R-value tested and verified in accordance to ASTM 518 by an independent lab. <sup>3</sup> Calculated door section R-value. <sup>4</sup> It is your responsibility to make sure your door meets local building codes. <sup>5</sup> For complete warranty details, visit amarr.com or contact your local Amarr dealer. <sup>6</sup> PVDF (Kynar) and powder coat finish warranty. \*Price upcharge applies.