

# 40' WIDE DOORS



## Ideal for Agricultural and Large Machinery

- Available in 2" and 3" polyurethane insulated steel doors  
Amarr 2042 & 2742  
Amarr 2743 **NEW 3"**
- Designed to handle 90MPH wind pressures
- 8" specially designed trusses have very high strength-to-mass ratios making them light weight and very strong
- Proprietary hinge saddle 5/8" roller carrier system minimizes stress on the end hinges by segregating hinge and roller carrier loads
- 5/8" long stem rollers for superior strength and long life
- Height and width combinations up to 2200 pounds total door weight without a standard dual shaft requirement or center cable pick-ups



[www.amarr.com](http://www.amarr.com)

**ENTRE/MATIC**

Entrematic  
165 Carriage Court  
Winston-Salem, NC 27105  
800.503.DOOR  
[www.amarr.com](http://www.amarr.com)



Door specifications and technical data subject to change without notice.

Sectional door products from Entrematic may be the subject of one or more U.S. and/or foreign, issued and/or pending, design and/or utility patents.

Entrematic and Amarr as words and logos are registered trademarks owned by Entrematic Group AB or companies within the Entrematic Group.

©Entrematic Group AB 2019. All rights reserved. Printed in USA Form #6140219/10M/GVS